Hogue's Rubber Automatic Grip features add up to improved scores, comfortable shooting and dependable service.

- COBBLESTONE[™] system is an efficient, non-slip, non-irritating stippling pattern that replaces conventional checkering.
- Hogue's Automatic Pistol Grips feel soft and resilient in your hand, yet are molded with reinforcing inserts which engage directly with the firearm frame and grip screws for a rock-solid grip-to-frame fit.

HOGUE

P.O. Box 91360 Henderson, NV 89009 805-239-1440 • Fax 805-239-2553 Hogueinc.com

The Originator and Maker of Monogrip®

IMPORTANT CONSUMER AND WARRANTY INFORMATION ON BACK OF PACKAGE

 Before starting to work, MAKE SURE THE FIREARM IS UNLOADED.

- Remove existing grip screws using appropriate tool. Remove old grip panels.
- 3. Place new grip panel into position and hand tighten into place using grip screws. Repeat for other side. We recommend using Blue Loctite threadlocker on the grip screw threads. This product cures when confined in the absence of air fittina between close metal surfaces. It protects threads from rust and corrosion and prevents loosening from shock and vibration.

IMPORTANT!

Check all functions of your firearm after grip is installed. **Test fire your firearm.** This is especially important if the firearm is to be used for law enforcement duty.

A FEW WORDS ABOUT FIT

It is a fact that frame dimensions vary from firearm to firearm. No grip is shipped from our facility unless it fits **our** firearms properly. Please keep this in mind. Because of frame variations, an occasional misfit may be encountered. Don't be alarmed! If your grip does not fit your firearm's frame to your satisfaction, we will do whatever it takes to fit your grip, or exchange it for one that will. Most often a simple phone call will remedy the situation. Before you call, make sure you have read the instructions and installed the grip properly.

It is imperative to make sure that every firearm functions properly with after-market grips installed. It is especially important on any firearm that the grip comes in close proximity to working components such as the mainspring trigger bar, etc. Although the grip functions properly on our firearms, it is the user's responsibility to assure that the grip functions properly on the firearm fitted with a new grip. If you do not feel competent to check the proper function yourself, we suggest visiting your gunsmith to check this for you. It is important to test fire any firearm fitted with new grips before using in the field.

If you have any problems installing your Hogue Grip please call us at (805) 239-1440. We will be glad to help make sure your grip fits perfectly.

CRD-INS-R4 1006201